



HYDRAULIC 2-POST LIFT





Exceeds the strict specifications of the DIN EN 1493:2010





HYDRAULIC 2-POST LIFT

POWER LIFT HF 3S 5000

Comfort and speed

The POWER LIFT HF 3S features NUSSBAUM's NT and patented HyperFlow® technology: The exceptionally fast lifting time as well as the low maintenance (no cables, no pulleys) will save you time and money. These technologies also guarantee maximum safety. A top quality lift for a safe and efficient workshop

Flexible

- ✓ No floor connection
- ✓ No static connection between the columns: Adjustable in width (+200 mm) and height, flexible height extension from +200 up to +900 mm can be provided

Practical design

- ✓ Precise control with NUSSBAUM commander and lockable main switch.

 Adjustable lowering speed
- ✓ Oil submerged motor: long lasting and quiet
- ✓ The 4 pulling cylinders are well protected: No risk of damage
- ✓ Compressed air and electric outlet (220V) on the column

Different versions suited to your needs

- Symmetric lifting arms


3 stage, symmetric lifting arms especially designed for SUVs and vans with long wheelbase

- Symmetric double-jointed arms (DG)

Symmetric carrying arms with two joints. With the DG arms you will have two lifts in one. The DG design allows to lift any type and size of vehicle, from very small cars to long transporters

POWER LIFT HF 3S 5000 with DG arms

Covers all vehicles from short wheelbase SMART or BMW MINI to long wheelbase Mercedes Benz SPRINTER or Volkswagen CRAFTER




Precise positioning

Smooth operation and variable lowering speed thanks to our NUSSBAUM commander



POWER LIFT HF 3S 5000: YOUR BEST ALLY TO LIFT A WIDE RANGE OF VEHICLES



Symmetric lifting arms

Double-jointed (DG) lifting arms


FAST, FASTER, HF 3S

- Lifting and lowering time 31 seconds / 15 seconds
- Low electricity consumption
- NT technology: 4 cylinders and 2 independent hydraulic circuits
- **HyperFlow**® **technology**: Automatic purging of the hydraulic system, automatic synchronization of the arms in the highest position
- Less moving parts, less maintenance



MEASURED FOR SUCCESS

POWER LIFT HF 3S	5000
Lifting capacity (kg)	5000
Lifting/lowering time approx. (sec)	31/15
Lifting height (mm) Version DG	2055
Version Symmetric	2067
Lowest lifting point (mm) Version DG	120-195
Version Symmetric	120-195
Total height (mm)	4020
Total height with optional extension (mm)	4020-4879
Total recommended width (mm)	3750
Column distance (mm)	3090
Arm-extraction long (mm) Version DG	0-1825
Version Symmetric	860-1850
Power supply (V/Hz)	400/50/16



ACCESSORIES



Height adapter round



Adapter for Mercedes SPRINTER



Adapter U-form for Mercedes-Sprinter



Lashing straps (2 units)



Drill holder



Drive-on tables (4 units)

More accessories available

Techn. changes and errors excepted. | Valid from 09 2020 © Nussbaum Custom Lifts GmbH | Hertzstr.6 | 77694 Kehl | Germany Tel.: +49 (0) 7853 899 – 0 | Fax: +49 (0) 7853 8787 | info@nussbaum-group.de | nussbaumlifts.com





