Automatic tyre changer VAS 741065A

GTIN: 4057612923599

SKU: 812862

Kendo.30 Premium | Leverless, including pneumatic bead depressor pusher and pneumatic wheel lift, passenger car, rim diameter 10 – 30" | wdk certified

DESCRIPTION

10 - 30" leverless tyre changer, featuring the patented Butler mounting tool for a stress-free mounting and demounting of all tyres and rims (Standard, UHP, RunFlat)

- Patented extra grip central center post:
  - Also suitable for reverse rims
  - Clamping the wheel is quick and requires minimum effort thanks to a self-clamping wheel support the self-locking mechanism of the floating plate

- Synchronised positioning of the two bead breaker rollers and mounting tool in one movement - Quick and safe bead breaking by using two opposite and synchronised rollers disks
- Patented mounting head made of scratch-proof material for damage-free work close to the edge of the rim (zero-stress effect)

- User-friendly console
- Indent button for correct and safe bead breaking without damaging the tyre side wall or the pressure sensor
- User-defined speed
- Inverter with speed limiter to protect tyre

- Quick-clamping lock Quick-fit rim clamping device
- Bead pusher arm
- Pneumatic wheel lift

Accessories on request:

- Universal flange for wheels without centre hole, also suitable for rims with extreme drop centre

ACCESSORIES

Top mounting head for rims with protruding spokes
G1000A142

Grease paste for tyre mount/ dismount | 3.5 kg
G800A37

Brush Plastic
G800A38

Rubber protection for support plate
G1000A81K
Rubber guards for reversed wheels | 1 set / 10 pieces

Bead protection foils | WDK approved
G1000A100K
Included in WDK kit | 1 set / 50 pieces

Wulstboy with towing device Standard
G1000A140
Included in WDK kit

Extension for bead depressor to 28 | for G1000A32
G1000A36
Included in WDK kit



Flange for LT (Light Truck)
G1000A101

Product 388615
388615

Cone with spacer | for 40 shaft | Ø 69 mm
G1000A126
Requiring G1000A80 - G1000A138

DELIVERY

Plastic protection for rim flange
G800A32
Bead protection for “Run Flat” tyres | Included in WDK kit | 1 piece



Extension for bead depressor to 28 | for G1000A32
G1000A36
Included in WDK kit

Bead protection foils | WDK approved
G1000A100K
Included in WDK kit | 1 set / 50 pieces

Wulstboy with towing device Standard
G1000A140
Included in WDK kit

DELIVERY

Top mounting head for rims with protruding spokes
G1000A142

Product 388684
388684

Wheel lift with stop in position
G1000A99NP

TECHNICAL DETAILS

Mounting head design	Without tire lever
Mounting arm design	Moveable
Mounting column design	Rigid
wdk certification	standard
TeqLink	Not possible
Workshop-Net	Not possible
Clamping device design	central
Min. clamping capacity	10"
Max. clamping capacity	30"
Max. rim width	15"
Tire type passenger car	Run-Flat
Max. wheel width	381mm
Max. wheel diameter	1143mm
Max. wheel weight	80kg
Min. working range of the mounting head	10"
Max. working range of the mounting head	30"
Automatic bead-breaking movement	Yes
Bead breaker force	12kN
Rotation speed	0 - 16rpm
Max. torque	1177Nm
Power inverter motor	1,5kW

Automatic tyre changer VAS 741065A

Driving power	0,75kW
Electrical connection	200/265 V, 50 - 60 Hz
Phases	1
Fuse protection	16A slow-blow
Air supply	8bar
Max. air supply	10bar
Width	1490mm
Depth	1600mm
Height	2060mm
Weight	424kg