



Electronic monitor wheel balancer VAS 741071

SKU: 810014

Librak 355PWS Premium | Touchscreen, Laser line H6, cone set, cone for SUV, passenger car, rim diameter 10 – 30" | Grey (RAL 7040)

DESCRIPTION

- Indicates the weight positioning with a laser line at 6 o'clock (for adhesive weights)
- Pressing a button moves from the outside to the inside unbalance position
- Automatic wheel width sonar for measuring the wheel width
- LED light
- Electronic wheel balancer with pneumatic clamping device
- Automatic measuring of distance and diameter by internal 2D measuring arm
- Automatic start by lowering the wheel guard
- The machine automatically stops the wheel in the outside unbalance position
- 19" monitor
- Quickly operational thanks to automatic program sequence and automatic locking in position of the outer counterweight
- ECO-WEIGHT program
- Programs: ALU-S, DYN, STATIC, SPLIT, SPOKE

Electronic monitor wheel balancer VAS 741071

2 / 4

Supplied standard accessories:

- SUV cone Ø 95 - 124 mm
- Passenger car cone set Ø 44 - 104 mm


General accessory parts on request:

- Wheel lift
- Precision flange

ACCESSORIES




Centering cones for passenger car
GAR111
Incl. protection cup | Ø 44 - 112 mm | 1 set /
3 pieces



Product 366464
366464



Automatic wheel width gauge
GAR301




Centering cone
GAR112
For off-road vehicles | Ø 95 - 132 mm

DELIVERY




Centering cones for passenger car
GAR111
Incl. protection cup | Ø 44 - 112 mm | 1 set /
3 pieces



Product 366464
366464



Automatic wheel width gauge
GAR301



Centering cone
GAR112
For off-road vehicles | Ø 95 - 132 mm

TECHNICAL DETAILS

Wheel data recording	Semi-automatic
Colour	7040RAL
Tread depth measurement	Optional
TeqLink	Not possible
Workshop-Net	Not possible
Measuring speed	< 100rpm
Measuring time	6s
Balancing accuracy +/-	1g
Display	TFT
Min. rim width	1,5"
Max. rim width	22"
Min. rim diameter	10"
Max. rim diameter	30"
Max. wheel diameter	1120mm
Max. wheel weight	70kg
Electrical connection	110/230 V, 50 – 60 Hz
Phases	1
Width	1188mm
Depth	1009mm
Height	1697mm