



Tyre changer HP441SQ.22


GTIN: 5063084201102

SKU: ROT.HP441.201102


Mounting head and mounting lever, automatic, square standard chucking table, incl. plastic protection for ALU rims, passenger car, rim diameter 10 – 24.5", max. rim width 12" | Red (RAL 3002) | for all tyre types with max. wheel diameter 41" (1050 mm)

DESCRIPTION


ACCESSORIES




Product 370449
370449




Product 387066
387066




Product 366578
366578




Product 367394
367394




Product 370527
370527




Product 367526
367526




Product 368253
368253




Product 386371
386371



Product 370455
370455



Product 370431
370431




Product 366458
366458




Helper arm pneumatic | with rotating arm

PLUS83H


Pneumatic device for bead pushing-raising with rotating arm




Product 369243
369243




Product 367406
367406




Product 370203
370203



Product 369837
369837

ACCESSORIES

Product 365537

365537


Product 387064

387064


Plastic protection for mounting head | Leverless

G800A8K

Tool protection package for alloy wheels | 10 sets


Bead lever protection for bead lever | 1 set / 50 pieces

G1000A13K


Plastic protection for bead breaker blade

G800A11

ALU protection for side bead breaker | 1 piece


Plastic protection for bead breaker blade

G800A11K

ALU protection for side bead breaker | 5 pieces


Bead-locking clamp

G84A13


Grease paste for tyre mount/dismount | 3.5 kg

G800A37


Bead depressor roller | 45° inclined

G800A49

To be used with G800A51


Bead depressor roller | 45° inclined

G800A51

To be used with G800A49 | necessary G800A119 for PLUS83H (WDK configuration)



Plastic protection for clamping jaws 20 – 22

G800A98K

Alloy wheels protections | 10 sets / 40 pieces


Extension for bead depressor for run-flat tyres

G800A114


Extension for bead depressor to 28 | for G1000A32

G1000A36

Included in WDK kit


Helper arm pneumatic | with rotating arm and WDK bead pressing device

PLUS83H/D

PLUS83 with WDK bead pressure device

ACCESSORIES



Additional side arm with cylindrical roller | without disc

G800A116

Accessory for tyre changers



Additional side arm with disc

G800A119

Accessory for tyre changers | No optional hexagonal arm!



Wheel clamps tips

G800A122


Renewable | for tyre changers | 1 set / 8 pieces



Helper arm pneumatic | with rotating arm

PLUS73


Pneumatic device for bead pushing-raising with rotating arm



Mounting lever | half moon-shaped


G1000A160

DELIVERY




Product 367514

367514



Product 369903

369903



Product 365729

365729



Plastic protection for clamping jaws 20 – 22

G800A98

Alloy wheels protections | 1 set / 4 pieces



Plastic protection for mounting head | Quick insert

G800A117

Tool head press-in protections for alloy wheels | 1 set



Mounting lever Standard

G1000A52

Passenger cars

TECHNICAL DETAILS

Mounting head design With tire lever

Mounting arm design Swiveling

Mounting column design Rigid

Colour 3002RAL

TeqLink Not possible

Workshop-Net Not possible

Clamping device design Clamping plate

Min. clamping capacity 10"

Max. clamping capacity 22"

Min. inner clamping range 12"

Max. inner clamping range 24,5"

Min. outer clamping range 10"

Max. outer clamping range 22"

Max. rim width 12"

Min. rim diameter 10"

Max. rim diameter 24,5"

Tire type passenger car Run-Flat

Max. wheel width 381mm

Max. wheel diameter 1050mm

Max. wheel weight 80kg

Automatic bead-breaking movement Yes

Bead breaker force 12kN

Tyre changer HP44ISQ.22

6 / 6

Number of mounting speeds	2
Rotation speed	6,5 / 13rpm
Max. torque	1200Nm
Power inverter motor	1,5kW
Chuck motor rating	0,75kW
Driving power	0,8 / 1,1kW
Electrical connection	230/400 V, 50 Hz
Phases	3
Fuse protection	16A slow-blow
Air supply	8bar
Max. air supply	10bar
Width	1320mm
Depth	1449mm
Height	1813mm
Weight	214kg
Country of Origin, customs	IT