



Tyre changer HP641SD.24 Pro

GTIN: 5063084200891

SKU: ROT.HP641.200891

Mounting head and mounting lever, automatic, square standard chucking table, incl. pneumatic bead depressor pusher and plastic protection for ALU rims, passenger car, rim diameter 10 – 26.5", max. rim width 15" | Red (RAL 3002) | for all tyre types with max. wheel diameter 43" (1092 mm) | wdk certified

DESCRIPTION

ACCESSORIES



Clamping jaws Plastic protection
G800A131



Plastic protection for mounting head
G800A132K

Tool protection package for alloy wheels | 1 set



Upgrade kit to leverless mounting
G800A82

To turn traditional tyre changers into leverless type



Plastic protection for bead breaker blade
G800A11K

ALU protection for side bead breaker | 5 pieces



Plastic protection for mounting head | Quick insert
G800A117K


Tool head press-in protections for alloy wheels | 10 sets



Bead lever protection for bead lever | 1 set / 50 pieces
G1000A13K



Bead-locking clamp
G84A13



Product 390495

390495



WulstBoy with pulling device and bead chain up to 24x
G1000A32



Extension for bead depressor for run-flat tyres
G800A114




Inflation gun without pressure-reducer quick inflating valve
G84A1

Tyre inflation device for tyre changers



Wheel lift pneumatic
G800A35



Tray kit for valves/accessories | with fixing pipe
G800A77



Kit for quick change of all tools | without tool
G800A70

G800A70 reduces max working range by 2x

ACCESSORIES



Mounting head for passenger cars | plastic

G800A72

For models with quick coupling device | with wheel hub for swinging quick coupling



Mounting head for passenger cars | plastic

G800A126

No quick change of tool head | for all models | complete with attachment to be connected directly to the hex shaft



Mounting head for passenger cars | pivoting | plastic

G800A73

For models with quick coupling device | with wheel hub for swinging quick coupling



Mounting head for motorcycles | plastic

G800A74

For all models with quick coupling | with wheel hub for quick coupling



Mounting head for ATV wheels

G800A76

For all models with quick coupling | equipped with quick coupling device



Shaft coupling for quick change tool

G800A75

For all models with quick coupling



Wheel clamps tips

G800A122

Renewable | for tyre changers | 1 set / 8 pieces



Plastic protection for clamping jaws 20 – 22

G800A98K

Alloy wheels protections | 10 sets / 40 pieces

DELIVERY



Helper arm pneumatic | with rotating arm and WDK bead pressing device

PLUS83H/D


PLUS83 with WDK bead pressure device



Bead depressor roller | 45° inclined

G800A49

To be used with G800A51



Device to limit the bead breaker stroke for WDK homologation

G1000A115



Plastic protection for bead breaker blade

G800A11

ALU protection for side bead breaker | 1 piece


DELIVERY



Plastic protection for mounting head | Quick insert

G800A117

Tool head press-in protections for alloy wheels | 1 set



Mounting lever | half moon-shaped

G1000A160



Plastic protection for rim flange

G800A32

Bead protection for "Run Flat" tyres | Included in WDK kit | 1 piece



Extension for bead depressor to 28" | for G1000A32

G1000A36

Included in WDK kit



Bead protection foils | WDK approved

G1000A100K

Included in WDK kit | 1 set / 50 pieces



Grease paste for tyre mount/dismount | 3.5 kg

G800A37



Brush Plastic

G800A38

TECHNICAL DETAILS

Mounting head design With tire lever

Mounting arm design Moveable

Mounting column design Tilttable

Colour 3002RAL

wdk certification Standard

TeqLink Not possible

Workshop-Net Not possible

Clamping device design Clamping plate

Min. clamping capacity 10"

Max. clamping capacity 24"

Min. inner clamping range 12"

Max. inner clamping range 26,5"

Min. outer clamping range 10"

Max. outer clamping range 24"

Max. rim width 15"

Min. rim diameter 10"

Max. rim diameter 26,5"

Tire type passenger car Run-Flat

Max. wheel width 381mm

Max. wheel diameter 1092mm

Automatic bead-breaking movement No

Bead breaker force 36kN

Tyre changer HP641SD.24 Pro

6 / 6

Rotation speed	0 / 16rpm
Max. torque	1200Nm
Driving power	0,75kW
Electrical connection	200 - 240 V, 50 - 60 Hz
Phases	1
Fuse protection	A slow-blow
Width	1467mm
Depth	1885mm
Height	2000mm
Weight	220kg
Country of Origin, customs	IT